

Fabric Data Sheet

Product : **SC5511655** Style : 8HS Customer Spec:

Description : 368GSM/8HS/T300 3K 40A - SMS47(Aero)/1655mm

Warp Fibre	AF	Fibre	Ends/10cm
	AF013	T300 3K 40A - SMS47	
	#REF!	#REF!	91.5
		#####	±3.9
Weft Fibre	AF	Fibre	Picks/10cm
	AF013	T300 3K 40A - SMS47	
	#REF!	#REF!	90.5
		#####	±3.9
Leno Yarn	K29/220Dtex Twisted (AF175)		

Tolerances/Testing/Frequency

Product Quality Plan

A

Check	Test Method	Nominal	Tolerance.
Mass	001/2/8	368	±10 gsm
Width	003	1655	-0, +7mm
Ends/10cm	004/005	91.5	
Picks/10cm	004/005	90.5	±3.9
Picks/Inch	010	22.99	
Check	Test Method	Maximum	
Weft Bow	006	30 mm/mt width	
Warp Bow	007	5 mm/mt length	
Nominal Length (metres)		142	
Construction	012	Verify	
Thickness	011	Verify	

Test Methods details refer to information as set in Sigmatex Quality Manual

Special Instruction :

This document is un-controlled and is not subject to any up-dates which
Sigmatex may undertake in the future